

INSULATION MICROSPHERES AND METHOD OF MANUFACTUREPatent Number: ☐ WO9607538Publication
date: 1996-03-14

Inventor(s): MARTIN ALFRED J.; PIDORENKO JOHN

Applicant(s): THERMACELL TECH INC (US)

Requested
Patent: ☐ EP0781196 (WO9607538), A1, A4Application
Number: WO1995US11340 19950906Priority Number
(s): US19940300961 19940906IPC
Classification: B32B5/16; B32B9/00; B32B15/02; B32B17/02; B32B17/04; B32B27/02; B32B27/04; B01J13/02;
B01J13/04; B01J13/20; B01J13/22; C23C14/00; C23C14/58; C23C20/02; C23C20/04; C03B19/10;
C03B19/12; C03B19/14; C03B37/00; C03C17/06; C03C17/34; C03C17/36; C03C25/02; C03C25/04EC
Classification: B29C70/66, B01J13/04, C09D5/00, C09D7/12S, F16L59/06C

Equivalents: AU3547895, JP10508261T

Cited
Documents: US3607169; US4303732; US4303736; US4303061; US4582756; US3769770; US4039297

Abstract

Evacuated microspheres (10) and insulating materials constructed from such microspheres (32) provide insulation and reduce heat transfer through radiation, conduction and convection. Additionally, an infrared reflective coating (16) is provided on a microsphere surface to reduce radiant heat transfer. A protective exterior coating (18) is also provided to protect an exteriorly applied infrared reflective coating on such a microsphere. The evacuated microspheres are used in elastomeric roof coatings or exterior paints.

Data supplied from the esp@cenet database - I2

FIG 1

1/2




FIG 2





FIG 3

2/2

FIG 4